# OPERATING UNIT FOR "SF<sub>6</sub> MONITORING MANAGER" SOFTWARE



Monitoring system for connection to digital weighing scales and filling devices with portable case

## B195R30 Operating unit for "SF<sub>6</sub> Monitoring Manager" Software

This operating unit is a useful tool for the stock management of  $SF_6$  cylinders and containers in connection with the " $SF_6$  Monitoring Manager" database software. The integrated interface allows the connection of the operating unit to all DILO weighing scales and gas refilling devices equipped with a serial interface for data exchange or monitoring.

The device is portable and can therefore be used on different sites and allows access to the central monitoring database via LAN/ WLAN connection.

Incoming and outgoing gas vessels are identified by means of the integrated barcode scanner. The barcode labels for clear identification of the vessels can be printed on site with the label printer.

The monitoring system considerably simplifies the stock management of gas quantities currently in use for switchgear production or at utility companies. Thus, the time-consuming manual registration of  $SF_6$  gas quantities in use is no longer an issue.

For more information on the "SF<sub>6</sub> Monitoring Manager" software please see our separate data sheet.





The operating unit can be easily connected to digital DILO weighing scales or gas refilling devices.

- 10" tablet computer with database connection via LAN/WLAN
- Interface for electronic weighing units and gas refilling devices
- 2D capable cordless barcode scanner with Bluetooth interface
- Thermal transfer printer for label width to 100 mm
- Stable plastic case

## OPERATING UNIT FOR "SF<sub>6</sub> MONITORING MANAGER" SOFTWARE



## B195R30 Operating unit for "SF6 Monitoring Manager" Software

Technical data:

Dimensions: L 610 mm, W 470 mm, H 280 mm
Weight: 17 kg
Operating voltage: 100 - 240 V / 50 - 60 Hz alternating current

#### Standard equipment:

10" tablet computer with database connection via LAN/WLAN
Thermal transfer printer for label width to 100 mm
2D capable cordless barcode scanner with Bluetooth interface
Black transport case
Operating manual

Important note: The device can only be operated in connection with the "SF<sub>6</sub> Monitoring Manager" software.

### SF<sub>6</sub> Monitoring Manager:

Web-based data software for  $SF_{_{\!\!6}}$  gas monitoring (cloud solution or installation on internal server)

Initial installation	B195R10
Annual user fee including updates and online support	B195R11

### Optional accessories at an extra charge:

Additional operating manua

Packing:

Packing for B195R30

3-775-R027-C

6-0004-R213