



■ ELECTRONIC BOTTLE SCALES

For determination of the fill quantity of gas bottles

K091R65 (Standard)

Electronic bottle scales

Digital display with battery compartment (IP54)

K091R67 (Comfort)

Electronic bottle scales

Digital display with internal rechargeable batteries (IP65)

Integrated serial interface for data exchange or monitoring

The electronic bottle scales allow quick and easy determination of the filling capacity of a gas bottle. The large weighing platform and the supporting chain provide additional stability of the gas bottle. The weight is indicated on the illuminated display which switches off automatically if the scales are not used for a certain time. Thanks to the tare function high precision quantification of gas inputs and outputs is possible. The bottle scales can be folded easily and compactly in one step after use.



- Weighing range: up to 120 kg with tare function
- Digit increment: 10 g
- Accuracy: ± 20 g
- Weight indication reversible from kg to lbs



ELECTRONIC BOTTLE SCALES



K091R65 (K067

Electronic bottle scales

Technical data K091R65:

Dimensions (if device is ready for operation): L 390 mm, W 450 mm, H 790 mm
Dimensions of weighing platform: L 300 mm, W 310 mm
Dimensions (if device is folded up): L 790 mm, W 450 mm, H 85 mm
Weight: approx. 15.8 kg
Power supply: a) Plug 100 - 240 V / 50 - 60 Hz with 2 meter long cable (only K091R65) b) Batteries (4 x 1.5 V AA) / Not included in the delivery
Protection class: IP54
Operating temperature: -10 to +40 °C

Technical data K091R67:

Dimensions (if device is ready for operation): L 390 mm, W 450 mm, H 790 mm
Dimensions of weighing platform: L 300 mm, W 310 mm
Dimensions (if device is folded up): L 790 mm, W 450 mm, H 118 mm
Weight: approx. 15.8 kg
Power supply: internal battery (12 V / 2.5 Ah) with battery charger / running time in continuous operation up to 20 hours
Protection class: IP65
Operating temperature: -10 to +40 °C

Standard equipment:

Surface: electrogalvanizing
Operating manual
Plug 100 - 240 V / 50 - 60 Hz with 2 meter long cable (only K091R65)

Optional accessories at an extra charge:

4 m long cable with M12 plug connectors for serial data exchange (only K091R67)	05-1602-R304
Additional operating manual	6-0004-R213

Packing:

Packing for K091R65 / K091R67	3-775-R033-C
-------------------------------	--------------

