

MINI SERIES C4/C5



For professional handling of gas mixtures

C4-B093R30

Vacuum compressor unit for gas mixtures with 3M™ Novec™ 4710^{*)}

Operating voltage: 220 - 240 V / 50 - 60 Hz alternating current

C5-B093R30

Vacuum compressor unit for gas mixtures with 3M™ Novec™ 5110^{*)}

Operating voltage: 220 - 240 V / 50 - 60 Hz alternating current

For recovery in conjunction with compressor only



Technical data:

Dimensions: Length 510 mm, Width 325 mm, Height 290 mm
Weight: 24 kg

Standard equipment:

Vacuum compressor for recovery of gas mixtures (3.3 m ³ /h [at 50 Hz]; 3.9 m ³ /h [at 60 Hz], final vacuum < 5 mbar)
Solenoid valve
Pressure sensor
Digital vacuum indication (0 - 400 mbar)
DILO couplings DN8
Electric control
2 m long electrical connecting cable
Paint: green (RAL DESIGN 120 70 70)
Operating manual

Optional accessories at an extra charge:

2 m long wire braided hose DN8 with DILO coupling tongue part DN8 on both ends (M28) - C4	C4-6-1130-R020
2 m long wire braided hose DN8 with DILO coupling tongue part DN8 on both ends (M24) - C5	C5-6-1130-R020
5 m long wire braided hose DN8 with DILO coupling tongue part DN8 on both ends (M28) - C4	C4-6-1130-R050
5 m long wire braided hose DN8 with DILO coupling tongue part DN8 on both ends (M24) - C5	C5-6-1130-R050
Aluminium transport case	3-781-R017

Spare parts kit:

Spare parts kit for vacuum compressor	05-1647-R100
---------------------------------------	--------------

Packing:

Packing for C4/C5-B093R30	3-748-R003-C
---------------------------	--------------

^{*)} 3M and Novec are registered trademarks of 3M.

