

MINI SERIES C4/C5



Portable vacuum pump unit for the evacuation of air

C4/C5-B078R09 (with ball valve)

Operating voltage: 208 - 240 V / 50 - 60 Hz alternating current

C4/C5-B078R09S15 (with ball valve)

Operating voltage: 110 - 127 V / 60 Hz alternating current

C4/C5-B078R19 (with solenoid valve)

Operating voltage: 208 - 240 V / 50 - 60 Hz alternating current

C4/C5-B078R19S15 (with solenoid valve)

Operating voltage: 110 - 127 V / 60 Hz alternating current



Technical data:

Dimensions: Length 435 mm, Width 270 mm, Height 370 mm
--

Weight: 29 kg

Standard equipment:

Vacuum pump for evacuation of air 16 m ³ /h (at 50 Hz) and 19 m ³ /h (at 60 Hz), final vacuum < 1 mbar
--

DILO couplings DN20

Ball valve or solenoid valve DN20

Digital vacuum indication (0 - 400 mbar)
--

3 m long electrical connecting cable

Operating manual

Optional accessories at an extra charge:

5 m long wire braided hose DN8 with coupling tongue part DN8 (M28) on one end and coupling tongue part DN20 (M48) on the other end - C4	C4-6-1173-R050
---	----------------

5 m long wire braided hose DN8 with coupling tongue part DN8 (M24) on one end and coupling tongue part DN20 (M43) on the other end - C5	C5-6-1173-R050
---	----------------

Aluminium transport case	3-781-R024
--------------------------	------------

Spare parts kit:

Annual maintenance kit for vacuum pump	6-1048-R111
--	-------------

Packing:

Packing for C4/C5-B078R..	3-748-R003-C
---------------------------	--------------

